



RPM	MODELLO MODEL	PORTATA FLOW		PRESSIONE PRESSURE		POTENZA POWER		PESO WEIGHT	
		l/min	GPM	bar	PSI	HP	kW	Kg	
PWC 13/12 S	950	8.5	2.3	120	1800	2.6	1.9	5.2	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	1450	13.0	3.4	120	1800	4.0	2.9	5.2	
MWC 15/20 S	950	10.0	2.6	200	3000	5.1	3.8	9.1	
	1450	15.0	4.0	200	3000	7.7	5.7	9.1	
MWC 20/20 S	950	13.1	3.5	200	3000	6.7	4.9	9.1	
	1450	20.0	5.3	200	3000	10.3	7.5	9.1	
GWC 30/20 S	950	19.7	5.2	200	3000	10.1	7.4	15.2	
	1450	30.0	7.9	200	3000	15.4	11.3	15.2	
GWC 50/12 S	950	31.5	8.3	120	1800	9.7	7.1	16.2	
	1450•	48.0	12.7	120	1800	14.8	10.9	16.2	

• Minimo 0.1 bar (1.5 PSI) di pressione in entrata / Min. 0.1 bar (1.5 PSI) inlet pressure

Dimensioni d'ingombro (mm) - Overall Dimensions (mm)

Modello/Model pag./page

PWC 13/12 S	11
MWC 15/20 S	13
MWC 20/20 S	13
GWC 30/20 S	14
GWC 50/12 S	15